

The Semijoin algebra

Peer-reviewed author version

VAN DEN BUSSCHE, Jan (2006) The Semijoin algebra. In: Dix, J. & Hegner, S.J. (Ed.) Foundations of Information and Knowledge Systems, Proceedings. p. 1-1..

DOI: 10.1007/11663881_1

Handle: <http://hdl.handle.net/1942/1426>

The semijoin algebra

Jan Van den Bussche

Universiteit Hasselt

Abstract

When we replace, in the classical relational algebra, the join operator by the semijoin operator, we obtain what we call the semijoin algebra. We will show that, when only equi-joins are used, the semijoin algebra is equivalent with the guarded fragment of first-order logic, and thus it inherits many of the nice properties of the latter logic. When more general theta-joins are used, however, we move outside the realm of guarded logics, and we will show how the notion of guarded bisimilarity can be extended accordingly. Last but not least, we show how the semijoin algebra can be used as a tool to investigate the complexity of queries expressed in the relational algebra, where we are mainly interested in whether or not a relational algebra expression for the query needs to produce intermediate results of nonlinear size. For example, we will show that the division operation cannot be expressed by a linear relational algebra expression.

This talk is a survey of work done in collaboration with Dirk Leinders, Jerzy Tyszkiewicz, and Maarten Marx.

References

1. D. Leinders, M. Marx, J. Tyszkiewicz and J. Van den Bussche. The semijoin algebra and the guarded fragment. *Journal of Logic, Language and Information*, 14:331–343, 2005.
2. D. Leinders and J. Van den Bussche. On the complexity of division and set joins in the relational algebra. *Proceedings 24th ACM Symposium on Principles of Database Systems*, pages 76–83. ACM Press, 2005.
3. D. Leinders, J. Tyszkiewicz and J. Van den Bussche. On the expressive power of semijoin queries. *Information Processing Letters*, 91:93–98, 2004.